

GATOR BLOCK BOND

ONE OF THE STRONGEST POLYURETHANE ADHESIVES ON THE MARKET



XP XTRA PERFORMANCE POLYURETHANE, LOW VOC

Gator Block Bond XP Polyurethane Adhesive, Low VOC is one of the strongest polyurethane adhesives on the market. It is specially formulated for overlays, pool copings, steps and wall caps, concrete pavers, stones, retaining walls, masonry units and bricks.

GATOR BLOCK BOND ADHESIVE is one of the strongest polyurethane adhesives on the market. It is especially formulated for bonding concrete, natural stones, blocks, bricks and pavers. **GATOR BLOCK BOND ADHESIVE** is intended to provide a permanent bond to approved materials. **GATOR BLOCK BOND ADHESIVE** can be used on dry or humid surfaces. Drying times vary depending on factors such as humidity, porosity, temperature and materials bonded together. **DIRECTIONS:**

1. Make sure that the surfaces you are bonding together are clean.
2. Cut the spout and puncture a hole in the cartridge with a nail.
3. Using a caulking gun, apply **GATOR BLOCK BOND ADHESIVE** on the clean surfaces.
4. Join the two surfaces firmly, use twisting motion. **GATOR BLOCK BOND ADHESIVE** works at above-freezing temperatures. Material may be repositioned up to 30 minutes without losing bond strength. Moisture will shorten the open time of polyurethane adhesives. Avoid use when raining or onto standing water. Coverage: Provides approximately 86 linear feet of 1/4" bead.

HAZARD STATEMENT: Causes eye irritation. Causes skin irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer. May cause damage to organs (olfactory organs) through prolonged or repeated exposure (inhalation).

PRECAUTIONARY STATEMENT: Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. **IF IN EYES:** rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. **IF INHALED:** if breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician. Store locked up. Dispose of contents/container to hazardous or special waste collection point.

IN CASE OF EMERGENCY: Call CHEMTREC 800-424-9300 or 703-527-3887 outside the US. In Canada, call CANUTEC 613-996-6666. ATTENTION: Read SDS before using. KEEP OUT OF THE REACH OF CHILDREN! FOR PROFESSIONAL USE ONLY. NOT FOR SALE TO OR USE BY THE GENERAL PUBLIC.



FORMULATED FOR
PERMANENT BONDING
OVERLAYS & POOL COPINGS
FAST CURE TIME
STEPS & WALL CAPS
FIRE PITS (UP TO 400°F)
RETAINING WALLS
MASONRY UNITS
STONES & BRICKS
CONCRETE PAVERS
DRY & DAMP SURFACES
DURABILITY

